

## EC - IP6030U 5MP POE 7" PTZ IP Underwater Camera/White Light



### Key Features:

- 1/2.7" 5MP CMOS Sensor
- Support Onvif
- f=5-90mm 18X optical zoom
- Max.128 preset,8 cruise routes,Preset position dwell time adjustable 2-10sec
- With power off memory function,cleaningscraper
- Pan:360° continuously; Pan 0.1-30° /ses,Tilt 0.1
- White light Distance: 30m ( ir leds optional)
- Underwater depth 30m Max
- IP68, POE

## Technical specifications:

<b>Image sensor</b>	
Sensor	1/2.7" CMOS
Effective Pixels	2592x1944
Minimum illumination	Color 0.1Lux/F1.4
<b>Function</b>	
Light distance	30m
Electronic shutter	1/50(1/60)s-1/100,000s
Lens	Focus f=5-90mm(F1.8-3.2) 18X optical zoom
Lens mount	M12
<b>Image resolution</b>	
Main Stream	2592x1944@15fps
Sub Stream	704x576@25fps
<b>General protocol</b>	
Protocol	HTTP/Onvif/DHCP/DDNS/NTP
<b>Interface</b>	
Wired	10Base-T/100Base-TX
Network Protocol	RJ45
<b>Other</b>	
Power supply	POE IEEE802.3at/af
Size	320 x 240 x 420mm
Operation temperature	-10°C- +60°C
Material	Stainless steel 316L
Cable	CAT6
Net Weight	N.W.19kg +cable 0.12kg/m