

Model		EC-IP3856U
Camera Type		2.0MP real-time underwater IP Camera
Camera	Image Sensor	1/2.7" 2MP Aptina CMOS
	Effective Pixels	1920x1080
	Min.Illumination	Color 0.1Lux/F1.4
	Electronic Shutter	1/50(1/60)s-1/100,000s
	Lens	2.1/3.6/4.2mm Lens
	Lens Mount	M12 Mount
	Material	stainless steel 316L
Compression	Compression Standard	H.265++/H.265+/H.265/H.264
	Video Frames	PAL/NTSC 5MP@1~30FPS
	Video stream output	Support adjustable stream 0.1M ~ 10Mbps
Image	Quality	3D-DNR,BLC,AWB,auto ISO
	Resolution	Main Stream:
		1920x1080 30fps(2MP),1280x720(1MP) 30fps Sub Stream:640x360,720x480(1-30fps)
Network	Parameter Settings	WEB configure and OSD supported, Real time recording, Transmission and playback
		Basic
	Protocol	HTTP/Onvif/DHCP/DDNS/NTP
	Alarm	Support Motion Detection, Linkage Alarm, Linkage recording, Sensor trigger alarm functions
Interface	Video Output	RJ45
	Network Interface	1 RJ45 Ethernet interface, 10/100M adaptation
Other	Work Environment	-10°C- +60°C
	Waterproof Criterion	IP68
	Power Supply	POE IEEE802.3at/af
	Size	64x64x26mm
	Cable	CAT6
	Net Weight	N.W.65kg +cable 0.12kg/m