

EC-IP8655U

4K IP Underwater PTZ POE Camera

Key features:

- 1/1.8 inch 8Megapixel progressive scan CMOS Sensor
- 3840*2160@60fps
- IP68, POE Max. water depth: 100m
- Focus f=2.7-14mm(F1.8-3.2) 5X Optical zoom
- Multiple network monitoring: Web viewer, CMS
- Max.32 preset.support preset recover if power off or dislocationHousing material: stainless steel 316L
- Attachment bar: adjustable by 180
- Toughened safety glass (ESG)
- TVS lightning protection to avoid 1.5KW thunderstrike



| Model | | EC-IP8655U |
|-------------|----------------------|--|
| Camera Type | | 4K IP Underwater PTZ POE Camera |
| Camera | Image Sensor | 1/1.8" 8MP scan CMOS Sensor |
| | Effective Pixels | 8MP 3840*2160 |
| | Min.Illumination | Color 0.5Lux/F1.4 |
| | Electronic Shutter | 1/50(1/60)s-1/100,000s |
| | Lens | 2.7-14mm(F1.8-3.2) 5XOptical zoom |
| | Lens Mount | M12/CS Mount |
| | Material | stainless steel 316L |
| Compression | Compression Standard | H.265+/H.265/H.265/H.264 |
| | Video Frames | PAL/NTSC 8MP@1-60FPS |
| | Video stream output | Support adjustable stream 0.1M ~ 10Mbps |
| Image | Quality | 3D-DNR,BLC,AWB,auto ISO |
| | Resolution | Main Stream: 8MP 3840*2160@60fps; 5MP 2592*1944@25fps;4MP 2560*1440@25fps;3MP 2048*1536@25fps |
| | | Sub Stream: 704*576@25fps |
| Network | Parameter Settings | WEB configure and OSD supported, Real time recording, Transmission and playback |
| | | Basic |
| | Protocol | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP |
| | Alarm | Support Motion Detection, Linkage Alarm, Linkage recording, Sensor trigger alarm functions |
| | | |
| Interface | Video Output | RJ45 |
| | Network Interface | 1 RJ45 Ethernet interface, 10/100M adaptation |
| PTZ | Pan / tilt | Pan 355 degree , Tilt 0-90degree |
| | Manual Speed | 0.5360/s ~360 /s continuously adjustable |
| Other | Work Environment | -10°C- +60°C |
| | Waterproof Criterion | IP68 |
| | Power Supply | POE IEEE802.3at/af |
| | Size | Ø 160 x 150 mm |
| | Cable | CAT6 |
| | Net Weight | 0.75 kg (NG) |